



Electric Shallow Well Pump (Output 100W/130W/250W)



Features



P H138/P H258

Rust-Resistant

The inside of pressure tank is doubly coated with the materials which is hard to be rusted, and guarantees the longer life.

Durability

The temperature thermostat defends the pump from abnormal high temperature.

By using the gunmetal in the pump, it prevents the generation of rust or corrosion and improves the reliability and the product life.

Easy maintenance

When replacing by a purchase, the cap nut will be convenient and will make the replacement be easier.

Specifications

Model	P H108	P H138	P H258
Output (W)	100	130	250
Input (W)	195	280	500
Suction head (m)	MAX.9	MAX.9	MAX.9
Discharge head (m)	9	10	14
Capacity (L/min)	16	21	33
(At total head m)	12	12	12
Pressure Switch (kgf/cm ²)	ON	1.0	1.6
	OFF	1.6	2.6
Suction Pipe (mm)	20	20	25
Discharge Pipe (mm)	20	20	25
Net Weight (kg)	12.2	14.3	22.0
Net Dimensions (mm)	Φ318×402	Φ318×461	Φ366×538
Gross Weight (kg)	13.2	15.5	24.0
Gross Dimensions (mm)	384×384×446	384×384×506	456×456×617
Specification Curve			

Specifications and design are subject to change without notice for improvement.

Distributed by

Produced by



KPS Industry Co.,Ltd.
Factory & head office
9-1-3 Seikadai Seikacho Souraku-gun
Kyoto 619-0238 Japan



Electric Shallow Well Pump (Output 400W/600W)



Feature



P H408/P H608 pumps, with more 400W class has the pilot pressure tanks to provide the high performance.

This advanced design eliminates the need for the additional air and ensures stable operation under a wide variety of conditions.

The circuit Breaker is provided to protect the motor from the overcurrent.

Adoption of parts for environment.
gun-metal (CAC407)
Cadmium-less brass Cr3 Plating

Specifications

Model	P H408	P H608
Output (W)	400	600
Input (W)	720	1010
Suction head (m)	MAX.9	2~MAX.8
Discharge head (m)	17	15~20
Capacity (L/min)	43	65
(At total head m)	12	12
Pressure Switch (kgf/cm ²)	ON	1.9
	OFF	2.8
		1.7~2.2
		2.3~2.8
Suction Pipe (mm)	30	30
Discharge Pipe (mm)	30	30
Net Weight (kg)	38.5	42.5
Net Dimensions (mm)	400×685×501	400×685×501
Gross Weight (kg)	40	44.0
Gross Dimensions (mm)	444×444×760	444×444×760
Specification Curve		

Specifications and design are subject to change without notice for improvement.

Distributed by

Produced by



KPS Industry Co.,Ltd.
9-1-3 Seikadai, Seika-cho, Souraku-gu
Kyoto, 619-0238 Japan